



SPECIFICATION SHEET

148-7000

TOP GRAIN GOATSKIN LEATHER PROTECTOR FOR NOVAX® GLOVES – GAUNTLET CUFF

- Top grain goatskin leather construction is the softest, most abrasion-resistant leather and is highly recommended for applications requiring tactile sensitivity
- Top grain leather is smooth, provides durability and dexterity
- Split leather gauntlet cuff for added forearm protection and allows for fast removal
- Straight thumb increases comfort in closed-fisted work
- Nylon strap with buckle for a secure, personal fit
- Cotton color binding denotes sizing

APPLICATIONS

- For use with Class 3-4 rubber insulating Novax® gloves. Cover glove to be used only for mechanical protection for rubber insulating gloves. Not to be used for electrical protection per ASTM F696-06 - 2011.

TECHNICAL DATA

MATERIAL	Goatskin, 100% leather			
COLOR	■ Natural			
CUFF STYLE	Gauntlet Cuff			
SIZES	9 - 12			
PACKAGING	12 per dozen, 24 pair per case			
CASE DIMENSIONS	15.2" x 15.2" x 8.1" / 38.5cm x 38.5cm x 20.5cm			
CASE WEIGHT	9	10	11	12
	15.4 lbs 7.0 kg	16.5 lbs 7.5 kg	17.6 lbs 8.0 kg	18.7 lbs 8.5 kg
COO	China			

MAX USE VOLTAGE

CLASS	AC VOLTS	DC VOLTS
3 - 4	25,500 - 36,000	39,750 - 54,000

10 NOVAX™ by G.B. INDUSTRIES
ANSI / ASTM CLASS 3 MADE IN MALAYSIA TYPE 1
MAX USE VOLT 26500V AC

10 NOVAX™ by G.B. INDUSTRIES
ANSI / ASTM CLASS 4 MADE IN MALAYSIA TYPE 1
MAX USE VOLT 36000V AC

BARCODES

ITEM	BAG	DOZEN	CASE
■ 148-7000/9	---	01616314081612	02616314081611
■ 148-7000/10	---	01616314081582	02616314081581
■ 148-7000/11	---	01616314081599	02616314081598
■ 148-7000/12	---	01616314081605	02616314081604



DIMENSIONS (in/cm)

	9	10	11	12
A	12 / 30.5	12 / 30.5	12 / 30.5	12 / 30.5
B	5.3 / 13.5	5.5 / 14	5.7 / 14.5	5.9 / 15
H	■ Green	■ Brown	■ Blue	■ Black

Leather Thickness: 0.8mm / Cuff Thickness: 1.6mm

