

# 3M 7600506



## Details

- Complete 60 ft. (18.3 m) system includes tensioner, energy absorber and anchors
- Lightweight 11/16" (17.5mm) static kernmantle rope lifeline
- Two 6 ft. (1.8m) tie-off adaptor anchors included
- Extremely lightweight and portable design
- Built-in energy absorber limits fall arrest forces
- Integral rotary tensioner for easy set-up
- Flexible system capacity of 2 workers
- Various lengths are available to suit jobsite needs
- Equipped with i-Safe™

60 ft. (18.3m) kernmantle rope horizontal lifeline system with tensioner, energy absorber, two 6 ft. (1.8m) tie-off adaptors and carrying bag.

The synthetic Sayline™ system is extremely lightweight, easy to install. Engineered with DBI-SALA® attention to quality and detail, the Sayline™ systems will work alongside you during maintenance, bridgework, construction and general industry applications with absolute safety and reliability. A horizontal lifeline may appear to be a basic line strung between two anchors, but it is not. It is critical to choose a system that has been precision engineered and rigorously tested to meet regulations. These systems are used to protect workers operating in the horizontal plane who may not have continuous access to suitable anchorage points.

## Specifications

Brand	Sayline™
Case Quantity	1
Install Type	Temporary/Portable
iSafe Equipped	Yes
Length	60 Feet
Lifeline Material	Kernmantle Rope
Max Number Of Users	2
Product Series	Sayline™
Product Type	Synthetic Horizontal Lifeline System
Recommended Industry	Construction, General Industrial, Mining, Oil & Gas, Transportation, Utilities
Span Type	Single-Span
Standards/Approvals	OSHA 1910.66, OSHA 1926.502
Weight	18 lb.
Weight Capacity	310 lbs. (141 kg)