

# StanSolv AF-15

## DESCRIPTION AND GENERAL PROPERTIES

- Material Nitrile
- Length (inches) 12
- Thickness (inches) 0.015 (15 mil)
- Wrist Straight cuff
- Colour/Color Green
- Interior finish Flocked
- Exterior finish Embossed texture
- Size / EAN 7 8 9 10 11
- Packaging 12 pairs/bag - 72 pairs/carton



## PERFORMANCE RESULTS

Certification category 3

CE 0334



JKL

4101

### Legends



**MECHANICAL HAZARDS EN 388**

PERFORMANCE LEVELS  
 0-4 0-5 0-4 0-4  
 └─ Abrasion resistance  
 └─ Blade cut resistance  
 └─ Tear resistance  
 └─ Puncture resistance



**LOW CHEMICAL PROTECTION EN 374**



**MICRO-ORGANISMS EN 374**



**RADIOACTIVE CONTAMINATION EN 421**



**HEAT AND FIRE EN 407**

PERFORMANCE LEVELS  
 0-4 0-4 0-4 0-4 0-4 0-4  
 └─ Burning behaviour  
 └─ Contact heat resistance  
 └─ Convective heat resistance  
 └─ Radiant heat resistant  
 └─ Resistance to small drops of molten metal  
 └─ Resistance to large quantities of molten metal



**SPECIFIC CHEMICAL PROTECTION EN 374**

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS EN 511**

PERFORMANCE LEVELS  
 0-4 0-4 0 or 1  
 └─ Convective cold resistance  
 └─ Contact cold resistance  
 └─ Water permeability

For more details: [www.mapa-pro.com](http://www.mapa-pro.com)

**MAPA**<sup>®</sup>  
 PROFESSIONAL  
[www.mapa-pro.com](http://www.mapa-pro.com)

## DESCRIPTION AND GENERAL PROPERTIES

- Excellent dexterity, for handling small objects
- Good grip on slippery objects, due to the embossed exterior finish
- Flock lining provides comfort and absorbs perspiration

## MAIN FIELDS OF USE

### Chemical industry

- Cleaning tanks
- Handling and transporting chemicals (solvents)

### Mechanical industry

- Assembly of small, oil and grease free parts
- Chemical treatment of metals
- Maintenance in wet environments (water, oil, greases, hydrocarbons)

## INSTRUCTIONS FOR USE

### Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
- Persons sensitized to dithiocarbamates and thiazoles should not use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website [www.mapa-pro.com](http://www.mapa-pro.com) or contact the Technical Customer Service - MAPA PROFESSIONNEL ([stc.mapaspontex@mapaspontex.fr](mailto:stc.mapaspontex@mapaspontex.fr)) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

### Storage conditions

Store the gloves in their original packaging protected from light, humidity and heat.

### Laundering conditions

Before taking off the gloves, clean them as appropriate :

- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
- in use with a solvent (alcohols, diluents, etc.) : rub over with a dry cloth
- in use with acids or alkalies : thoroughly rinse the gloves in use with under running water, and rub over with a dry cloth

Caution : improper use of the gloves or submitting them to any cleaning or laundering process which is not specifically recommended can alter their performance levels.

### Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

### Food contact US

FDA 21CFR 177.2600

## LEGISLATION

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council. This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate  
0072/014/162/04/06/0029

- Issued by the notified body nr  
0072

I.F.T.H. – Av. Guy de Collongue - F-69134 ECULLY CEDEX