

DEFENDER

Highly absorbent sonic bonded mat for oily spills and overspray



Features and Benefits

- Abrasion-resistant top layer gives pads and rolls strength for everyday cleanup jobs
- Perfect for medium-duty industrial, maintenance and general applications
- Quickly absorbs leaks, spills and overspray to keep floors dry
- Perforations allow you to tear pads and rolls into different sizes based on your application
- Oil selective — repels water but absorbs oil and all oil-based fluids
- Pads perforated at 7.5" up the center
- Rolls perforated every 7.5" vertically and cross-perforated at 17" horizontally

DEFENDER™ Mat

White Oil-Only Pads

Item #	Description	Size	Units/Pkg	Absorbs/Pkg
WPB100H	HeavyWeight Pads	15" x 19"	100	29.1 gal.
WPB50H	HeavyWeight Pads	15" x 19"	50	14.6 gal.
WPKB50H	HeavyWeight King Pads	30" x 30"	50	45.3 gal.
WPB100M	MediumWeight Pads	15" x 19"	100	24.7 gal.
WPB50M	MediumWeight Pads	15" x 19"	50	12.4 gal.
WPB200S	LightWeight Pads	15" x 19"	200	31.1 gal.
WPB100S	LightWeight Pads	15" x 19"	100	15.6 gal.

White Oil-Only Rolls

Item #	Description	Size	Units/Pkg	Absorbs/Pkg
WRB150H	HeavyWeight Roll	30" x 150'	1	55.2 gal.
WRSB150H	HeavyWeight Split Rolls	15" x 150'	2	55.2 gal.
WRB150M	MediumWeight Roll	30" x 150'	1	46.1 gal.
WRSB150M	MediumWeight Split Rolls	15" x 150'	2	46.1 gal.
WRB300S	LightWeight Roll	30" x 300'	1	59.1 gal.



DEFENDER Mat Construction

One layer of spunbond fabric is ultrasonically bonded to a single layer of meltblown sorbent.



HYC

Helps you comply with 29 CFR 1910.22(a)(2), 29 CFR 1910.107(b)(3), 29 CFR 1910.107(g)(2), 29 CFR 1910.120(j)(1), 29 CFR 1910.1450(e), and 49 CFR 173.12 (b)(2)(iv). See page 99 for details.