

DuraScrim™ Jacket

Stock Number - J56107

Compliance Standards: Flame resistant. Self extinguishing with flameout and afterglow less than or equal to 2 seconds after removal of ignition source and char length of less than 6 inches. Test Method ASTM D6413.



The jacket has modified batwing sleeve construction with a 90 degree sleeve-to-body angle, a storm fly front with snap closure, and an attached hood.



Garment Type: Designed to meet the protection and safety needs of customers who require durable selfextinguishing rainwear.

Sizes: S, M, L, XL, 2X, 3X, 4X, 5X

Color: Yellow

Material: Yellow material is 8 oz./yd² PVC on Polyester

Scrim.

Pockets:

Labels/Tags:

Label sealed to inside collar displays Tingley logo, size, Flame Resistance and country of origin. Care instructions, fabric composition, lot and date codes are located on the reverse.

Seam Construction: All seams are RF/heat sealed and

100% waterproof.

Closure Type: Snap closure with 4 snaps and storm fly

with 1 additional snap.

Packaging: Printed polyethylene bag.

Other: Mildew Resistant.

Dimensions	S	M	L	XL	2X	3X	4X	5X
Chest	45"	49"	53"	57"	61"	65"	69"	73"
Length	29"	30"	31"	31"	32"	32"	32"	33"
Sleeve Length	33.5"	34"	35"	35.5"	36"	36.5"	37"	37.5"

Case Pack: 12 each

	C	Dimon	alana	/Waiak	
ı	Lase.	Dimen	SIUUS	:/vveiar	١T

Case Diffierisions/Weight	
S = 15"(L) X 13"(W) X 9"(H) / 22 lbs.	2X = 15"(L) X 13"(W) X 9"(H) / 28 lbs.
M = 15"(L) X 13"(W) X 9"(H) / 24 lbs.	3X = 15"(L) X 13"(W) X 9"(H) / 29 lbs.
L = 15"(L) X 13"(W) X 9"(H) / 26 lbs.	4X = 15"(L) X 13"(W) X 9"(H) / 31 lbs.
XL = 15"(L) X 13"(W) X 9"(H) / 27 lbs.	5X = 15"(L) X 13"(W) X 9"(H) / 32 lbs.

DuraScrim™ is a trademark of Tingley Rubber Corp.